


Water heaters
Chauffage d'eau

FO / FA

Flanged Immersion heaters 150 lb ANSI
Thermoplongeurs à brides normalisées 150 lb ANSI



- Immersion heaters for water heating in usual industrial applications.
- 150 lb ANSI carbon steel flange, 2.1/2" or 3"
- 11 mm dia Incoloy 800 sheathed elements
- Watt density 9.3W / sq.cm
- Pocket for optional thermostat
- Polyamide terminal enclosure IP66 with 360° positioning
- Voltage 400V / 3Ph
- Thermoplongeurs pour chauffage d'eau industrielle.
- Bride acier suivant standard ANSI 150 lb 2"1/2 ou 3"
- Éléments blindés Incoloy 800, Ø11mm
- Charge 9,3 W/cm²
- Doigt de gant pour thermostat optionnel.
- Boîtier orientable polyamide IP66
- Alimentation 400V Tri



Flange size / Diamètre de la bride		Output Puissance	Length X Cote X	Cold NC	Weight Poids
NB 2,5"	NB 3"				
FO 00303/60	FA 00303/60	3000 W	200 mm	30 mm	6 kg
FO 00603/60	FA 00603/60	6000 W	365 mm	30 mm	7 kg
FO 00903/60	FA 00903/60	9000 W	525 mm	30 mm	7 kg
FO 01203/60	FA 01203/60	12000 W	685 mm	30 mm	7 kg
FO 01503/60	FA 01503/60	15000 W	850 mm	30 mm	8 kg
FO 01803/60	FA 01803/60	18000 W	1010 mm	30 mm	8 kg
FO 02403/60	FA 02403/60	24000 W	1345 mm	30 mm	9 kg
FO 03003/60	FA 03003/60	30000 W	1660 mm	30 mm	10 kg
FO 03603/60	FA 03603/60	36000 W	1985 mm	30 mm	11 kg

Option : Safety thermostat
(consult our sales office)

Option : Thermostat de sécurité
(nous consulter)

Note : Other available standardised range
with Watt density 3.9 W/sq.cm
(3 to 18 kW)

Nota : Autre gamme standardisée
disponible avec charge 3,9 W/cm²
(3 à 18 kW)

CONSULT OUR SALES OFFICE

NOUS CONSULTER