


FR

Immersion heaters with withdrawable elements Thermoplongeurs à éléments démontables



- Immersion heaters for industrial water where heating elements need to be replaced with a minimum of down time and no need to drain down system
- 150 lb ANSI carbon steel flange, 2.1/2"
- Stainless steel sheathed heating elements in stainless steel pockets
- Watt density 3,9W / sq.cm
- Polyamide terminal enclosure IP66 with 360° positioning
- Voltage 400V / 3Ph
- Thermoplongeurs pour chauffage d'eau industrielle lorsque l'application nécessite des remplacements rapides des éléments chauffants, sans vidange des systèmes.
- Bride acier suivant standard ANSI 150 lb 2"1/2.
- Éléments chauffants monotubulaires blindés Inox, sous doigts de gant Inox
- Charge 3,9 W/cm²
- Boîtier orientable polyamide IP66
- Alimentation 400V Tri

Reference / Référence	Output Puissance	Length X Cote X	Cold NC	Weight Poids
FR 00303/60	3 000 W	675 mm	85 mm	6 kg
FR 00603/60	5 000 W	970 mm	85 mm	8 kg
FR 00903/60	7 000 W	1 340 mm	85 mm	9 kg
FR 01203/60	9 000 W	1 610 mm	85 mm	10 kg



Note : FR Heaters are also standardized with flange ANSI 150 lb 6, 8, 10, 12, and 14" (output from 6 to 144 kW)
CONSULT OUR SALES OFFICE

Nota : Gamme FR également standardisée sur brides ANSI 150 lb 6, 8, 10, 12, et 14" (Puissance de 6 à 144 kW)
NOUS CONSULTER